1. Product And Company Identification

Manufacturer

NOX-CRETE MANUFACTURING INC 1444 SOUTH 20TH STREET

OMAHA, NE 68108

Contact Information

FAX Number: 402-341-9752 E-Mail: corporate@nox-crete.com Web Site: www.nox-crete.com

Emergency Phone Number CHEMTREC: 800-424-9300

CHEMTREC OUTSIDE OF U.S.: 703-527-3887

Manufacturer Phone Number

402-341-2080

Issue Date: 04/22/2013

Product Name: DURO-COLOR (All Colors)

Chemical Family: CONCENTRATED DYE SOLUTION

MSDS Number: 746 Product Code: DC

2. Hazards Identification

Primary Routes(s) Of Entry

Eye Contact, Ingestion, Inhalation, Skin Contact

Eye Hazards

May cause eye irritation.

Skin Hazards

May cause skin irritation.

Ingestion Hazards

Aspiration hazard if swallowed. Can enter lungs and cause damage.

Inhalation Hazards

May be harmful if inhaled.

3. Composition/Information On Hazardous Ingredients

Ingredient Name	CAS Number	
CHROMIUM, COPPER or COBALT COMPLEX DYES	Trade Secret	
PROPRIATARY GLYCOL ETHER	Trade Secret	
PROPRIATARY SURFACTANTS	Trade Secret	

Pursuant to 29CFR 1910.1200 the specific chemical identity is being withheld as Trade Secret, while all health and safety properties and effects are included in the MSDS.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water. Wash clothing before reuse. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

4. First Aid Measures - Continued

Ingestion

If swallowed, do not induce vomiting. Get medical attention immediately.

Inhalation

If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.

5. Fire Fighting Measures

Flash Point: > 200 °F > 93 °C Flash Point Method: PMCC

Extinguishing Media

Use CO2 (Carbon Dioxide), dry chemical, or foam.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear. Water can be used to cool and protect exposed material. Avoid spreading burning liquid with water used for cooling purposes.

6. Accidental Release Measures

Eliminate any ignition source. Dike or impound spilled material. Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect into vapor tight containers and dispose of properly.

7. Handling And Storage

Handling Precautions

Keep container closed when not in use. Use only with adequate ventilation.

Storage Precautions

Store product in a cool, dry environment away from sources of ignition.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate ventilation to keep product vapor concentrations below specified TLV.

Eye/Face Protection

Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury.

Skin Protection

Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

Respiratory Protection

General room ventilation is normally adequate. Avoid breathing the product mist. The use of a NIOSH approved respirator is recommended whenever the airborne concentrations exceed the TLV.

Ingredient(s) - Exposure Limits

CHROMIUM, COPPER or COBALT COMPLEX DYES

0.5 mg/m3 TWA OSHA PEL

PROPRIATARY GLYCOL ETHER

Not Established

PROPRIATARY SURFACTANTS

10 mg/m3 TWA

9. Physical And Chemical Properties

Appearance

Liquid with slight odor. Available in various colors.

Chemical Type: Mixture Physical State: Liquid

Boiling Point: 250-900 °F 120-480 °C Specific Gravity: Lighter than water

Packing Density: 8.1 lbs per gallon 0.97 kg per liter

Solubility: Soluble

Evaporation Rate: Slower than ether Flash Point: >200 F >93 C (PMCC)

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatible Materials

Strong oxidizing agents, strong acids and strong bases.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and nitrous oxide from incomplete combustion.

11. Toxicological Information

Chronic/Carcinogenicity

No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program, the U.S. Occupational Safety and Health Act, or the International Agency on Research on Cancer (IARC).

12. Ecological Information

Environmental Fate Information

Readily biodegradable when tested in accordance with the OECD 301/EPA OPPTS 835.3110 test protocols.

13. Disposal Considerations

Care must be taken to prevent environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

14. Transport Information

Proper Shipping Name

Not hazardous in containers less than 119 gallons.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are exempt from the TSCA Inventory requirements.

SARA Section 313 Notification

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

CHEMICAL MAX WEIGHT %

Glycol Ether Category (All colors)

Up to 57.0 % Up to 0.77 %

Chromium Compounds (Ink Black, Gun Metal Gray,

15. Regulatory Information - Continued

SARA Section 313 Notification - Continued

Quicksilver, Hemlock Green, Mint, Celery, Coral Blue, Royal Blue, Sundried Tomato, Pomegranate, Husker Red, Cabernet, Auburn, Pecan, Wheat, Tobacco Brown, Java, Shocking Fuchsia, Antique Gold, Aztec, Plum

Cobalt Compounds (Hemlock Green, Buckskin, Wheat, Tobacco Brown, Java, Pecan)

Up to 0.77 %

NFPA 2 1 0

- CIIVII	
HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	X

16. Other Information

Revision/Preparer Information

MSDS Preparer: Nox-Crete Manufacturing

Reference Documentation

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyers risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Disclaimer

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of this use thereof.

NOX-CRETE MANUFACTURING INC

Printed Using MSDS Generator™ 2000