MATERIAL SAFETY DATA SHEET

NOX-CARB SP COMPONENT B

Contact Information			
	Contact Information		
FAX Number: 402-341-9752 E-Mail: corporate@nox-crete.com			
			web Site: www.nox-cie
Manufacturer Phone N 402-341-2080	Manufacturer Phone Number 402-341-2080		
6			
	CAS		
	77-58-7		
	67-56-1		
gh the skin.			
headache, dizziness, naus epression. May cause tinglin em. May effect the blood an	ea, vomiting, ng and numbr d blood syste	nes	s in the hands
cause pulmonary edema (a	occumulation	of f	luid in the
	E-Mail: corporate@nox Web Site: www.nox-cre <u>Manufacturer Phone N</u> 402-341-2080	E-Mail: corporate@nox-crete.com Web Site: www.nox-crete.com <u>Manufacturer Phone Number</u> 402-341-2080 CAS Number 77-58-7 67-56-1 gh the skin. Irritation of the mouth, throat, and storr headache, dizziness, nausea, vomiting, epression. May cause tingling and number m. May effect the blood and blood system sed on results of animal studies.	E-Mail: corporate@nox-crete.com Web Site: www.nox-crete.com <u>Manufacturer Phone Number</u> 402-341-2080 CAS Number 77-58-7 67-56-1 gh the skin. . Irritation of the mouth, throat, and stomach headache, dizziness, nausea, vomiting, epression. May cause tingling and numbnes em. May effect the blood and blood system.

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

4. First Aid Measures - Continued

<u>Skin</u>

Remove contaminated clothing and shoes. Wash affected areas with soap and water. Wash clothing before reuse. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting. Get medical attention immediately. If victim is fully conscious, give one or two cups of water to drink. Never give anything by mouth to an unconscious victim.

Inhalation

If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.

5. Fire Fighting Measures

Flash Point: < 100 °F < 38 °C Flash Point Method: PMCC

Fire And Explosion Hazards

Can form flammable mixtures with air and flash at room temperature. Explosive hazard in fire situation. Vapor heavier than air may travel considerable distance to a source of ignition and flash back.

Extinguishing Media

Use CO2 (Carbon Dioxide), dry chemical, or foam.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear. Water can be used to cool and protect exposed material. Avoid spreading burning liquid with water used for cooling purposes.

6. Accidental Release Measures

Eliminate any ignition source. Dike or impound spilled material. Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect into vapor tight containers and dispose of properly.

7. Handling And Storage

Handling Precautions

Keep container closed when not in use. Use only with adequate ventilation.

Storage Precautions

Store product in a cool, dry environment away from sources of ignition.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate ventilation to keep product vapor concentrations below specified TLV.

Eye/Face Protection

Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury.

Skin Protection

Wear gloves and appropriate protective clothing as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

Respiratory Protection

General room ventilation is normally adequate. Avoid breathing the product mist. The use of a NIOSH approved respirator is recommended whenever the airborne concentrations exceed the TLV.

MATERIAL SAFETY DATA SHEET

NOX-CARB SP COMPONENT B

8. Exposure Controls/Personal Protection - Continued

Ingredient(s) - Exposure Limits

DIBUTYLTIN DILAURATE 0.1 mg/m3 TWA METHANOL 200 ppm TWA

9. Physical And Chemical Properties

Appearance

Water white with an organic solvent odor.

Chemical Type: Mixture Physical State: Liquid Specific Gravity: Heavier than water Packing Density: 9.0 lbs per gallon 1.08 kg per liter Solubility: Insoluble Evaporation Rate: Slower than ether VOC: < 250 grams per liter Flash Point: <100 F <38 C (PMCC)

10. Stability And Reactivity

Stability: Stable Hazardous Polymerization: Will not occur

Incompatible Materials

Avoid contact with acids, bases and oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, formaldehyde and methanol.

11. Toxicological Information

Chronic/Carcinogenicity

No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program, the U.S. Occupational Safety and Health Act, or the International Agency on Research on Cancer (IARC).

12. Ecological Information

No Data Available...

13. Disposal Considerations

Care must be taken to prevent environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

14. Transport Information

Proper Shipping Name

FLAMMABLE LIQUID N.O.S. (Petroleum Naptha)

Freight Class

3


MATERIAL SAFETY DATA SHEET

NOX-CARB SP COMPONENT B

15. Regulatory Information

SARA Section 313 Notification

This product does not contain any ingredients in concentrations at or above de minimis levels that are listed as toxic chemicals under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.



16. Other Information

Revision/Preparer Information

MSDS Preparer: David MacFarlane

This MSDS Supersedes A Previous MSDS Dated: 05/11/2005

Reference Documentation

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyers risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Disclaimer

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of this use thereof.

NOX-CRETE MANUFACTURING INC

Printed Using MSDS Generator™ 2000