

## TAG-ERASE



Powerful, biodegradable graffiti remover for use on non-porous surfaces such as vinyl covered signs, billboards and baked on painted surfaces.

### HOW IT WORKS

Tag-Erase combines a powerful combination of biodegradable and environmentally friendly solvents and surfactants that quickly penetrate, soften and lift graffiti from non-porous surfaces allowing it to be easily wiped away with a towel or cloth. Restores graffiti defaced surfaces to their original appearance without scrubbing.

### APPLICATIONS

- ◆ Use on all types of smooth, non-porous surfaces to include reflective, vinyl signs, baked on painted metal, galvanized steel, trash bins, mail boxes, windows, metal flashing, truck trailers, truck van boxes, railroad box cars and bulk tankers, etc.
- ◆ For use on most non-porous surfaces where graffiti is more difficult to remove using conventional graffiti removers.
- ◆ Can be used as an effective alternative to presealing with sacrificial or permanent graffiti barrier coatings.
- ◆ Tag-Erase can be safely used by government employees or contractors to control graffiti on road signs, metal utility structures, bus shelters, benches, bridge and rail signs, and other city, state and federal publicly funded buildings and structures.

### ADVANTAGES

- ◆ Quickly and effectively removes lacquer, enamel, acrylic, vinyl, alkyd, oil and other synthetic resin based spray or brush applied graffiti.
- ◆ Effective on most signs, decals, plastics, metal, glass, reflective surfaces and many other non-porous surfaces.
- ◆ Fast acting formulation performs well at all temperatures - even below freezing.
- ◆ Tag Erase is Green Engineered™ – better for health and safe for the environment.
- ◆ Tag-Erase is biodegradable and is safe for disposal in all municipal sewer treatment facilities.
- ◆ Following the application of Tag-Erase, unwanted graffiti can be easily wiped away with a towel or cloth.
- ◆ Tag-Erase does not contain any phenol, methylene chloride or other halogenated solvents.

### ▲ PRECAUTIONS ▲

- ◆ Tag-Erase contains very powerful solvents. Users of this product must wear protective gear to protect eyes, face, arms and body from spray mist and splatter.
- ◆ Tag-Erase may etch or dissolve some painted surfaces. Always test a small area before applying Tag-Erase.
- ◆ Do not use in the presence of open food stuffs.
- ◆ Protect all adjacent surfaces not to receive Tag-Erase from accidental splatter.
- ◆ Not for use in enclosed areas where ventilation is limited.
- ◆ Tag-Erase is not recommended for dilution with water or solvent prior to applications.
- ◆ Tag-Erase can cause permanent discoloration when applied to certain surfaces. Always perform a test in an inconspicuous area to confirm compatibility before large scale use of this product.
- ◆ Graffiti paint can crosslink over time making it more difficult to remove. Best results are obtained when graffiti is removed soon after it is applied.
- ◆ Test the surface to be cleaned with the pressure washer intended to be used to verify that the pressure washer does not cause any surface damage to substrate to be cleaned.
- ◆ The spray application of Tag-Erase requires the use of a sprayer equipped with EPDM (acetone-resistant) seals and gaskets

### USE INSTRUCTIONS

- ◆ Request current product literature, labels and material safety data sheets from manufacturer and read thoroughly before product use.
- ◆ Site environmental conditions, substrate conditions and construction have a major effect on product selection, application methods, procedures and rates, appearance and performance. Product literature provides general information applicable to some conditions. However, an adequate site test application by the purchaser or installer in advance of field scale use is mandatory (irrespective of any other verbal or written representations) to verify that product and quantities purchased can be satisfactorily applied and will achieve desired appearance and performance under intended use conditions.
- ◆ The user and all other people in the area near the application of Tag-Erase must wear protective safety gear



to protect eyes, face and body from spray mist and splatter (see Precautions).

- ◆ Protect all adjacent surfaces not requiring graffiti removal with plastic sheeting.
- ◆ Apply Tag-Erase to graffiti defaced substrate surface using a hand pump sprayer, airless sprayer, roller equipped with a 3/8 inch (9.0 cm) nap roller cover or brush. Typical application rates range from 100-200 sf/gal (2-5 sm/L) per coat. One or two coats is generally required for complete removal of all graffiti residue.
- ◆ Allow Tag-Erase to penetrate all the way through graffiti. Dwell times usually range from 10-20 minutes depending upon the severity of graffiti.
- ◆ To remove the graffiti, simply wipe away with a towel or cloth. For improved performance, wet the towel with a small amount of Tag Erase before wiping. Larger areas can be cleaned with a 2,000-3,000 (14-20 MPa) pressure washer.
- ◆ Do not allow Tag-Erase to dry on the surface. If Tag-Erase begins to dry, the surface should be recoated with Tag-Erase.

## TECHNICAL DATA

---

Density	8.2 lbs/gal (987 g/L)
Color	Water White
Odor	Mild
Flash Point	120° F (49° C)
Water Soluble	Yes
Biodegradable	Yes

## PACKAGING

---

Tag-Erase is packaged in 1 gal (3.8 L) jugs and 5 gal (19 L) pails.

## SHELF LIFE

---

Shelf life is one year. Use before the "USE BY" date stated on product packaging.

## HANDLING/STORAGE

---

Store in a dry location within a temperature range between 40° F (4° C) and 100° F (38° C).

## AVAILABILITY & TECHNICAL SERVICES

---

In addition to corporate offices in Omaha, Nebraska, NOX-CRETE Products Group maintains regional offices and distribution centers in principal markets throughout the world. For source or technical information, call 800-669-2738 or 402-341-2080.

## LIMITED WARRANTY

---

### NOTICE-READ CAREFULLY

#### CONDITIONS OF SALE

NOX-CRETE offers this product for sale subject to, and Buyer and all users are deemed to have accepted, the following conditions of sale and limited warranty which may only be varied by written agreement of a duly authorized corporate officer of NOX-CRETE. No other representative of or for NOX-CRETE is authorized to grant any warranty or to waive limitation of liability set forth below.

#### WARRANTY LIMITATION

NOX-CRETE warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, NOX-CRETE will replace the defective product with new product without charge to the purchaser.

NOX-CRETE makes NO OTHER WARRANTY, either express or implied, concerning this product. There is NO WARRANTY OF MERCHANTABILITY. In no case shall NOX-CRETE be liable for special, indirect or consequential damages resulting from the use or handling of the product and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which damages are claimed.

#### INHERENT RISKS

NOX-CRETE MAKES NO WARRANTY WITH RESPECT TO THE PERFORMANCE OF THE PRODUCT AFTER IT IS APPLIED BY THE PURCHASER, AND PURCHASER ASSUMES ALL RISKS ASSOCIATED WITH THE USE OR APPLICATION OF THE PRODUCT.